

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- ✱ • BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- ✱ • FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

STIRRER (OPTIONAL)

12


REACTION
VESSEL

10


14

THERMOSTATED
ALUMINUM BLOCK

MAGNETOSENSITIVE
REGION OF HALL
EFFECT PROBE 16



18



TO AUXILIARY DEVICES
(FFT ANALYZER,
MAGNETIC STORAGE)

INSTRUMENTATION, BLOCK DIAGRAM

FIG.1a

11 11 11




FIG. 1b

1c/15c




FIG. 1c




FIG.2.




FIG.3.




FIG.4.




FIG. 5.

21/30
5/23




FIG.6.




FIG.7.




FIG.8.




FIG.9.




FIG.10.




FIG.11.




FIG.12.




FIG.13.






FIG.14.



15/23

FIG.15.



15/33

FIG.16.




FIG.17.




FIG.18.




FIG.19.

~~20/23~~




FIG.20.




FIG.21.




FIG.22.

23/23
~~23/23~~





FIG.23.

FIGURE 4 24

Pour individual runs with hydrazine



Pour individual runs with a control bottle






FIGURE 25





FIGURE 26

Hydrazine Sulfate Runs - June 11, 17 and 19







FIGURE 27

Nov.25 Rm324 runs, K-P: '•', C:'o', Scatter of slopes 0 to [150 165 180 195 210 225 240] secs



K-P: '•', C:'o', Scatter of 95% Confidence Limits on slopes




FIGURE 28






FIGURE 19

(A)
COMPUTER-GENERATED
FACSIMILE OF CHART
RECORDING




(B)
ELIMINATION OF DENSITIES
BELOW AN ARBITRARY
THRESHOLD. SHOWN ON
COMPUTER SCREEN
FACSIMILE OF CHART
RECORDING




REPRESENTATIVE CALCULATIONS


- * number of densities: 136
- * number of densities with areas > 70 units: 22
- * Total area of densities: 5709 units
- * Total area of densities > 70 units: 2559 units





22+




2512









5 2734




6
2435





7 7426





9 24 88






H 240




1224




RUSTY PIPE 45"


1 min.




13 742




14 JUN




745




16 24 91




fn 46



247
+8



248



2.42